GNU/Linux most wanted

Summary of most useful commands

©Copyright 2006-2005. Free Electrons. Free to share under the terms of the Creative Commons Attribution-ShareAlike 2.5 license (http://creativecommons.org)

Sources, translations, updates, command and concepts details on our free training materials: http://free-electrons.com/training/intro_univ_linuv

Thanks to Michel Blanc, Hermann J. Beckers and Thierry

Latest update: Oct 27, 2009

Handling files and directories

Create a directory: Create nested directories:

mkdir -p dir1/dir2

Changing directories: cd newdir cd .. (parent directory)

cd - (previous directory) cd (home directory)

cd ~bill (home directory of user bill)

Print the working (current) directory:

Copy a file to another: cp source_file dest file

Copy files to a directory: cp file1 file2 dir

Copy directories recursively: cp -r source dir dest dir rsync -a source_dir/ dest dir/

Create a symbolic link: ln -s linked file link

Rename a file, link or directory: mv source file dest file

Remove files or links: rm file1 file2

Remove empty directories: rmdir dir

Remove non-empty directories: rm -rf dir

Listing files

List all "regular" files (not starting with .) in the current directory:

Display a long listing:

List all the files in the current directory, including "hidden" ones (starting with .):

List by time (most recent files first):

List by size (biggest files first)

List with a reverse sort order: 1s -r

Long list with most recent files last: ls -ltr

Displaying file contents

Concatenate and display file contents: cat file1 file2

Display the contents of several files (stopping at each page):

more filel file2 less file1 file2 (better: extra features)

Display the first 10 lines of a file: head -10 file

Display the last 10 lines of a file: tail -10 file

File name pattern matching

Concatenate all "regular" files:

Concatenate all "hidden" files: cat .*

Concatenate all files ending with .log:

List "regular" files with bug in their name:

List all "regular" files ending with . and a single character:

Handling file contents

Show only the lines in a file containing a given substring:

grep substring file

Case insensitive search: grep -i substring file

Showing all the lines but the ones containing a substring:

grep -v substring file

Search through all the files in a directory: grep -r substring dir

Sort lines in a given file: sort file

Sort lines, only display duplicate ones once: sort -u file (unique)

Changing file access rights

Add write permissions to the current user:

Add read permissions to users in the file group: chmod a+r file

Add execute permissions to other users: chmod o+x file

Add read + write permissions to all users: chmod a+rw file

Make executable files executable by all: chmod a+rX *

Make the whole directory and its contents accessible by all users: chmod -R a+rX dir (recursive)

Comparing files and directories

Comparing 2 files: diff file1 file2

Comparing 2 files (graphical): gvimdiff file1 file2 tkdiff file1 file2 kompare file1 file2

Comparing 2 directories: diff -r dirl dir2

Looking for files

Find all files in the current (.) directory and its subdirectories with log in their name: find . -name "*log*"

Find all the .pdf files in dir and subdirectories and run a command on each:

find . -name "*.pdf" -exec xpdf {} ':'

Quick system-wide file search by pattern (caution: index based, misses new files): locate "*pub*"

Redirecting command output

Redirect command output to a file: ls *.png > image files

Append command output to an existing file: ls *.jpg >> image files

Redirect command output to the input of another command: cat *.log | grep error

Job control

Show all running processes:

Live hit-parade of processes (press P, M, T: sort by Processor, Memory or Time usage):

Send a termination signal to a process: kill <pid> (number found in ps output)

Have the kernel kill a process: kill -9 <pid>

Kill all processes (at least all user ones): kill -9 -1

Kill a graphical application: xkill (click on the program window to kill)

File and partition sizes

Show the total size on disk of files or directories (disk usage): du -sh dir1 dir2 file1 file2

Number of bytes, words and lines in file: wc file (word count)

Show the size, total space and free space of the current partition: df -h .

Display these info for all partitions:

Compressing

Compress a file: gzip file (.gz format) bzip2 file (.bz2 format, better) lzma file (.1zma format, best compression)

Uncompress a file: gunzip file.gz bunzip2 file.bz2 unlzma file.lzma

Archiving

Create a compressed archive (tape archive): tar zcvf archive.tar.gz dir tar jcvf archive.tar.bz2 dir tar --lzma -cvf archive.tar.lzma

Test (list) a compressed archive: tar ztvf archive.tar.gz

tar itvf archive.tar.bz2 tar --lzma -tvf archive.tar.lzma

Extract the contents of a compressed archive: tar zxvf archive.tar.gz tar ixvf archive.tar.bz2 tar -- lzma -xvf archive.tar.lzma

tar options:

c: create + · test

x: extract

j: on the fly bzip2 (un)compression z: on the fly gzip (un)compression

Handling zip archives

zip -r archive.zip <files> (create) unzip -t archive.zip(test/list) unzip archive.zip (extract)

Printina

Send PostScript or text files to queue: lpr -Pqueue f1.ps f2.txt (local printer)

List all the print jobs in queue:

Cancel a print job number in queue: cancel 123 queue

Print a PDF file: pdf2ps doc.pdf lpr doc.ps

View a PostScript file: ps2pdf doc.ps xpdf doc.pdf

User management

List users logged on the system:

Show which user I am logged as:

Show which groups user belongs to:

Tell more information about user: finger user

Switch to user hulk: su - hulk

Switch to super user (root): su - (switch user)

su (keep same directory and environment)

Time management

Wait for 60 seconds: sleep 60

Show the current date:

Count the time taken by a command: time find charming prince -cute -rich

Command help

Basic help (works for most commands): grep --help

Access the full manual page of a command: man grep

Misc commands

Basic command-line calculator

Basic system administration

Change the owner and group of a directory and all its contents:

sudo chown -R newuser.newgroup dir

Reboot the machine in 5 minutes: sudo shutdown -r +5

Shutdown the machine now: sudo shutdown -h now

Display all available network interfaces:

Assign an IP address to a network interface: sudo ifconfig eth0 207.46.130.108

Bring down a network interface: sudo ifconfig eth0 down

Define a default gateway for packets to machines outside the local network: sudo route add default gw 192.168.0.1

Delete the default route: sudo route del default

Test networking with another machine: ping 207.46.130.108

Create or remove partitions on the first IDE hard disk-

fdisk /dev/hdal

Create (format) an ext3 filesystem: mkfs.ext3 /dev/hda1

Create (format) a FAT32 filesystem: mkfs.vfat -v -F 32 /dev/hda2

Mount a formatted partition: mkdir /mnt/usbdisk (just do it once) sudo mount /dev/ubal /mnt/usbdisk

Mount a filesystem image (loop device): sudo mount -o loop fs.img /mnt/fs

Unmount a filesystem: sudo umount /mnt/usbdisk

Check the system kernel version:







